AveLab

VALID TILL END OF JUNE 2024

All brand from



LED HOTPLATE, HP550-S PLATE SIZE: 7 X 7 INCH

LED screen display accurate temperature with maximum temperature up to 550 °C. Separate safety circuits with safety temperature of 580°C.

RM1,400.00



HIPETTE SINGLE-CHANNEL ADJUSTABLE

The DLAB new generation fully autoclavable mechanical pipette has the best ergonomic design and ultralight weight.

Available size:

2-20µL, 10-100µL, 100-1000µL, 2,000-10,000µL

RM450.00

BOTTLE TOP DISPENSER DISPENSMATE-PRO

Dispensers come with standard GL45 thread to suit Schott-Duran laboratory bottles. Supplied with GL25, GL28, GL32, GL38 & S40mm adapters to suit common bottles incl. Winchester. Fully autoclavable at 121°C

Available size: 2.5-25ml

RM900.00



LCD DIGITAL MAGNETIC HOTPLATE STIRRER, MS7-H550-S PLATE SIZE: 7 X 7 INCH

LCD displays actual temperature. Built-in PID controller ensures safe heating of the medium with overheating protection. Maximum heating plate temperature up to 550°C.

Free PT1000 external temperature sensor + support clamp.

RM1,480.00



4-CHANNEL DIGITAL MAGNETIC HOTPLATE STIRRER, MS-H340-S4

Independent heating and stirring control for each position. LCD display shows real-time temperature and speed PID controller ensures a precise and stable heating process (maximum temperature up to 340°C.

Free PT1000 external temperature sensor + support clamp.

RM5,800.00







VORTEX MIXER (ADJUSTABLE SPEED), MX-S

Comes with touch operation or continuous mode and variable speed control from 0 to 2500rpm.

RM600.00



MULTI-PURPOSE LOW SPEED CENTRIFUGE, DM0636

With swing-out bucket rotors and adapters that can be compatible with standard tubes up to 100mL at low speed. Speed can be set from 300- 6000rpm and maximum capacity of the centrifuge: 100 mLx4. Including swing-out rotor, 50ml basket with adaptor or 10-15ml basket with adaptor.

RM9,800.00



LCD DIGITAL MAGNETIC HOTPLATE STIRRER, MS10-H500-PRO PLATE SIZE: 10X 10 INCH

The external temperature control is possible by connecting the temperature sensor (PT1000) with an accuracy at±0.2°C and digital speed control of 100 ~ 1500rpm with LCD Display. The Max. heating plate temperature 500°C

RM2,400.00





VALID TILL END OF JUNE 2022



ORBITAL SHAKER, SK-O330-PRO

Have max. load capacity is 7.5kg(O330) with platform with double LCDs for independent display of time and speed.

RM4,800.00



10-POSITION MAGNETIC HOTPLATE STIRRER, MS-H-S10

10-position Classic Hotplate Magnetic Stirrer, stainless steel plate with silicone cushion, heating temperature up to 120°C with speed up to 1100rpm





PALM MINI CENTRIFUGE WITH BLUE LID, 7000RPM, D1008

Ideal for microfiltration and quick spin-downs with 7000rpm fixed speed. Including two rotors of A8-2 & A4-PCR8 and both adapter SA02P&SA05P2(package contain in the box).

RM620.00









