

FireLine® is universally used in Gyproc wall partitioning systems, wall linings and ceiling systems to give increased fire protection. The qualities of the plasterboard allows high-performance fire rated systems to be developed for fire rating up to 2 hours.

Gyproc emphasized on the importance of fire protection on Life Safety and Property Protection through hundreds of systems developed, tested and certified by local authorities.

CHARACTERISTICS

Gypsum plasterboard with fiberglass and micro silica in the core to improve the cohesive properties of the plasterboard at high temperatures.

RECOMMENDED USE

Universally used for wall and ceiling systems that requires fire performance.

PRODUCT FORMAT

Thickness	12.5mm*	15mm
Nominal Weight	10.50kg/m ²	12.45kg/m ²
Nominal Sheet Size	1220mm x 2440mm	
Edge Type	Recessed Edge	Square Edge
	RE C	SE

*Available upon request. Use as part of system component.

FIRE RATING

- Non-combustible in accordance to BS 476: Part 4
- Low fire propagation in accordance to BS 476: Part 6
- Class 1 surface spread of flame in accordance to BS 476:
 Part 7
- Classified as Class 0 material in accordance to BS 476: Part 6 & 7
- Complete GypWall and ceiling system able to provide up to 2 hours fire rating in accordance to BS 476: Part 22

MANUFACTURING SPECIFICATIONS

• In compliance with ASTM C1396M and BS EN 520

HANDLING AND WORKABILITY

- Lightweight
- Quick and easy installation

THERMAL INSULATION


 Recommended design thermal conductivity, k-value = 0.18 W/m.K

HEALTH AND ENVIRONMENTAL CONTRIBUTIONS

- Made from 100% natural gypsum
- Recyclable material, hence environmentally friendly and certified with Green Product Certification Scheme
- Does not produce toxic fumes or hazardous substance that are harmful to health
- Product is manufactured in a facility certified to standards of ISO 14001, ISO 45001

QUALITY ASSURANCE

• Product is manufactured in a facility certified to ISO 9001



SGBP 3367