

TopLine®

A standard gypsum plasterboard with ivory face paper that displays a smooth surface.



TopLine® has superior thermal insulation and non-combustible properties that are compliant with international standards.

Ceiling systems built with TopLine® opens a world of unlimited design possibilities allowing you to construct that beautiful architecture which encompasses pleasant acoustics, safety and reliability.



CHARACTERISTICS

A standard gypsum plasterboard with an aerated gypsum core encased and firmly bonded to stronger paper liners.

RECOMMENDED USE

Suitable to be used in dry areas ceiling applications.

PRODUCT FORMAT

Thickness	9mm	
Nominal Weight	5.25kg/m ²	
Nominal Sheet Size	1220mm x 2440mm	
Edge Type	Recessed Edge	Square Edge
		

FIRE RATING

- Non-combustible in accordance to BS 476: Part 4
- Low fire propagation in accordance to BS 476: Part 6
- Class 1 surface spread of flame in accordance to BS 476: Part 7
- Classified as Class 0 material in accordance to BS 476: Part 6 & 7

MANUFACTURING SPECIFICATIONS

- In compliance with ASTM C1396M and BS EN 520

AESTHETIC PROPERTIES

- Highly flexible in creating the highest standards of design
- Crack-free
- Easily decorated with paint, cornices, etc.
- Seamless and smooth finishing

HANDLING AND WORKABILITY

- Lightweight
- Quick and easy installation
- Applicable for curved ceiling installation down to a radius of 1.8m

HEALTH AND ENVIRONMENTAL CONTRIBUTIONS

- Made from 100% natural gypsum
- Recyclable material, hence environmentally friendly and certified with Green Product Certification Scheme
- Does not produce toxic fumes or hazardous substances that are harmful to health
- Product is manufactured in a facility certified to standards of ISO 14001, ISO 45001

QUALITY ASSURANCE

- Product is manufactured in a facility certified to ISO 9001

